

IOR Energy PTY LTD
 ABN 60 010 504 444
 PO Box 14 Bulimba
 Brisbane QLD 4171 Australia
 Telephone: (07) 3895 4444
 Facsimile: (07) 3395 7902
 Web: www.ior.com.au
 Email: mail@ior.com.au



PRODUCT SPECIFICATION

ENERSOL KA

| TEST | UNIT | TYPICAL | LIMIT | METHOD |
|--------------------------|---------|---------|------------------------|------------|
| Distillation Range | | | | |
| IBP | °C | 185 | | ASTM D86 |
| 5%* | °C | | 190 min | |
| 95%* | °C | | 280 max | |
| FBP | °C | 285 | | |
| Specific Gravity @ 15°C* | | 0.800 | 0.790 min 0.820 max | ASTM D1298 |
| Colour | Saybolt | >24 | | ASTM D156 |
| Flashpoint* | °C | | 76 min | ASTM D93 |
| Aromatics | vol% | <20 | | GC |
| Electrical Conductivity* | pS/m | | 70 min | ASTM D2624 |
| Aniline Point | °C | 67 | | ASTM D611 |

Properties marked with (*) will be tested and verified with the Certificate of Analysis.

Dangerous Goods Details

| | |
|----------------------|----------------|
| UN Number | Not applicable |
| Dangerous Good Class | Not applicable |
| Subsidiary Risk | Not applicable |
| Packing Group | Not applicable |
| Hazchem Code | Not applicable |