



## HyTank® - HT2 SPECIFICATIONS

IOR Petroleum Pty Ltd's range of HyTank self-bunded tanks are cost-effective storage solutions for Type 1 or 2 Combustible Fluids. These Tanks are manufactured to comply with Australian Standard AS1692 and when installed in compliance with Australian Standard 1940 for Storage of Combustible fluids easily meet most regulatory requirements.



- Double walled self-bunded tank
- Rugged construction with forklift pockets and lifting lugs for easy lifting and transport
- Fuel level Gauge
- Top fill point and access with tank venting
- Removable Cover allowing access to internal tank for cleaning
- Suction and return points for direct plumbing to generator sets
- 600mm square inspection hatch
- 1000mm 2" vent pipe and vent, removable for transportation
- Interstitial space venting with visual access to monitor for leakage
- Manufactured from 1st grade new steel, 3mm internal tank, 3mm external tank
- Total capacity Inner Tank 1950 litres
- Safe Fill Level 1950 litres
- Bare Tank Weight 1360 kgs
- Dimensions 1130mmW x 2500mmL x 1235mmH (excluding Vent Extension)

**PHONE** 1300 457 467  
**WEB** [www.ior.com.au](http://www.ior.com.au)  
**EMAIL** [sales@ior.com.au](mailto:sales@ior.com.au)

**IOR**  
 PETROLEUM