



HyTank® - HT85 SPECIFICATIONS

IOR Petroleum Pty Ltd's range of HyTank self bunded tanks are cost effective storage solutions for Type 1 or 2 Combustible Fluids. These Tanks are manufactured to comply with Australian Standard AS1692 and when installed in compliance with Australian Standard 1940 for Storage of Combustible fluids easily meet most regulatory requirements.



- Double walled self bunded tank
- Rugged construction with container pins for easy lift and transport (45ft Container footprint)
- Bunded Pump bay with flexibility for pump type and layout
- Calibrated dip stick
- Statutory signage
- Ladder and platform to access dip points and tank venting
- Overfill protection valve and Overfill alarm
- Antisyphon Valve
- Connection points for submersible pumps
- 2 x 600mm dia inspection hatches with internal ladders
- Twin counterweight masts for hose management
- 1500mm 2" vent pipe and vent with a bolt down for transportation
- Interstitial space venting and dip monitor for leakage
- Manufactured from 1st grade new steel, 6mm for both external and internal tanks
- Total capacity 87,660 litres
- Safe Fill Level 78,900 litres
- Bare Tank Weight 16,488kgs
- Dimensions 2438mmW x 13716mmL x 3200mmH

PHONE
WEB
EMAIL

1300 457 467
www.ior.com.au
sales@ior.com.au

IOR
PETROLEUM