

IOR Energy PTY LTD
 ABN 60 010 504 444
 PO Box 14 Bulimba
 Brisbane QLD 4171 Australia
 Telephone: (07) 3895 4444
 Facsimile: (07) 3395 7902
 Web: www.ior.com.au
 Email: mail@ior.com.au



PRODUCT SPECIFICATION

ENERSOL WS

TEST	UNIT	TYPICAL	LIMIT	METHOD
Distillation Range				
IBP	°C	145	142-158	ASTM D86
5%*	°C	152		
50%	°C	161		
95%*	°C	185		
FBP	°C		205 max	
Density @ 15°C*	Kg/L	0.771	0.755 min 0.790 max	ASTM D4052
Colour	Saybolt	30	26 min	ASTM D156
Flashpoint*	°C	38	31 min	ASTM D93
Sulphur	mg/kg	<10		ASTM D4294
Copper Corrosion		1a		ASTM D130
Benzene Content	vol%	≤0.01		GC
Aromatics	vol%	20		GC
Paraffins	vol%	70		GC
Electrical Conductivity*	pS/m		200 min	ASTM D2624
Aniline Point	°C	58		ASTM D611

Properties marked with (*) will be tested and verified with the Certificate of Analysis.

Dangerous Goods Details

UN Number	1268
Dangerous Good Class	3
Subsidiary Risk	Not applicable
Packing Group	III
Hazchem Code	3[Y]