

IOR Energy PTY LTD
 ABN 60 010 504 444
 PO Box 14 Bulimba
 Brisbane QLD 4171 Australia
 Telephone: (07) 3895 4444
 Facsimile: (07) 3395 7902
 Web: www.ior.com.au
 Email: mail@ior.com.au



PRODUCT SPECIFICATION

ENERSOL M

TEST	UNIT	TYPICAL	LIMIT	METHOD
Distillation Range				
IBP	°C	85		ASTM D86
5%*	°C		90 min	
95%*	°C		135 max	
FBP	°C	145		
Specific Gravity @ 15°C*		0.720	0.700 min 0.740 max	ASTM D1298
Colour	Saybolt	>26		ASTM D156
Flashpoint	°C	<0		ASTM D93
Benzene Content	vol%	<0.1		GC
Sulphur	mg/kg	<10		ASTM D4294
Copper Corrosion		1A		ASTM D130
Aromatics	vol%	<3		GC
Paraffins	vol%	>60		GC
Electrical Conductivity*	pS/m		200 min	ASTM D2624
Aniline Point	°C	63		ASTM D611

Properties marked with (*) will be tested and verified with the Certificate of Analysis.

Dangerous Goods Details

UN Number	1268
Dangerous Good Class	3
Subsidiary Risk	Not applicable
Packing Group	II
Hazchem Code	3[Y]E